

# Using Leak Sealer

## It's easy when you know how!

Small, hard-to-find leaks can be more than just annoying. Left untreated, water that has escaped can undermine your pool and equipment. While major leaks require structural repairs, minor leaks can be easily treated with **Leak Sealer** by Lo-Chlor®.

- Easily seals minor leaks in all swimming pool & spa plumbing materials
- Use in pools losing up to one inch of water per day
- Don't need to know where the leak is to treat it effectively
- No need to drain pool water
- Works in 24 hours
- Sells for a fraction of the cost of leak detection & repair service
- 1 quart treats 15,000 gallons

Simply pour into the pool or spa at the site of the leak. Don't know the leak's location? Pour the recommended dosage into the skimmer. **Leak Sealer** will start the sealing process upon contact with the leak.

For an average pool water volume of 15,000 gallons, use one quart of Leak Sealer. Follow these easy steps:

### **STEP 1:** Based on filter type:

The filter needs to be **by-passed** or the filter cartridge needs to be **removed** prior to treating the pool with Leak Sealer.

### **STEP 2:** Turn off the pump.

**STEP 3:** Add Leak Sealer into the skimmer. If you have two skimmers, add half a quart of Leak Sealer into one skimmer and the other half of the quart into the other skimmer.

**STEP 4:** Wait 30 minutes after adding Leak Sealer and then turn on the pump and run it for at least 4 hours. Set variable speed pump on lowest setting available.

**STEP 5:** After 24 hours, check the water level to determine if a second application of Leak Sealer is needed. If not, bathers can enter the pool.

*Try Leak Sealer today! Stop leaks, conserve water, save money and protect your pool and its surroundings.*



## COMMONLY ASKED QUESTIONS:

### Which type of materials does Leak Sealer work on?

The product is designed only to seal minor leaks in rigid materials, including PVC pipes, fittings, or another hard pipe. The application of the product requires water circulation during the process.

### Do I need to drain the pool?

No! Add Leak Sealer to the pool, and water circulation will do the rest. This saves you time and money.

### How long will Leak Sealer last in a pool?

Typically, users can expect the leak to remain sealed for roughly 6 months to a year, but this varies substantially from pool to pool and depends on the nature of the leak.

### When Leak Sealer finds the leak, what happens?

As Leak Sealer encounters air on the other side of the leak, it initially gels in that gap and then mineralizes, forming a water-tight plug. Some leaks, due to their size or shape (fewer than 10% of those encountered), may require a second application.

