



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /

Rules and Regulations

Revision Date: 05/06/2025

Date of issue: 08/06/2014

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: **Filter & Tile Cleaner (FAT123-12, FAT05-1, FAT015-1, TVS240-1)**

Intended Use of the Product

Cleaning Swimming Pool Filters and Tiles

Name, Address, and Telephone of the Responsible Party

Company:

Lo-Chlor, LLC

5841 Powerline Rd. Suite 202

Fort Lauderdale, FL 33309

954-491-9810

lo-chlor.com

Emergency Telephone Number

Emergency number : 1-800-424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Corr. 1A H314

Eye Dam. 1 H318

Aquatic Acute 3 H402

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



Signal Word (GHS-US) : Danger

Hazard Statements (GHS-US) : H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H402 - Harmful to aquatic life

Precautionary Statements (GHS-US) : P260 - Do not breathe mist, spray, vapors
P264 - Wash hands, forearms, and exposed areas thoroughly after handling
P273 - Avoid release to the environment
P280 - Wear eye protection, face protection, protective clothing, protective gloves
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P321 - Specific treatment (see Section 4)
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations

Revision Date: 05/06/2025

Date of issue: 08/06/2014

Version: 1.0

Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Name	Product identifier	% (w/w)	Classification (GHS-US)
Sodium xylene sulfonate	(CAS No) 1300-72-7	7 - 10.5	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Sodium metasilicate pentahydrate	(CAS No) 10213-79-3	5 - 9	Met. Corr. 1, H290 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335
Pentasodium triphosphate	(CAS No) 7758-29-4	3 - 7	Skin Irrit. 2, H315 Eye Irrit. 2B, H320
2-Butoxyethanol	(CAS No) 111-76-2	1 - 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Benzenesulfonic acid, C10-16-alkyl derivatives	(CAS No) 68584-22-5	1 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2A, H319 Aquatic Acute 2, H401

Full text of H-phrases: see Section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Immediately call a POISON CENTER or doctor/physician.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do not induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage.

Inhalation: May cause respiratory irritation.

Skin Contact: Highly corrosive to skin.

Eye Contact: Causes serious eye damage.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations Revision Date: 05/06/2025 Date of issue: 08/06/2014

Version: 1.0

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Thermal decomposition generates : Corrosive vapors.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Sulfur oxides.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s)

Cleaning Swimming Pool Filters and Tiles.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

2-Butoxyethanol (111-76-2)		
Mexico	OEL TWA (mg/m ³)	120 mg/m ³
Mexico	OEL TWA (ppm)	26 ppm
Mexico	OEL STEL (mg/m ³)	360 mg/m ³
Mexico	OEL STEL (ppm)	75 ppm
USA ACGIH	ACGIH TWA (ppm)	20 ppm



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
 Rules and Regulations Revision Date: 05/06/2025 Date of issue: 08/06/2014

Version: 1.0

USA OSHA	OSHA PEL (TWA) (mg/m ³)	240 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	24 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	5 ppm
USA IDLH	US IDLH (ppm)	700 ppm
Alberta	OEL TWA (mg/m ³)	97 mg/m ³
Alberta	OEL TWA (ppm)	20 ppm
British Columbia	OEL TWA (ppm)	20 ppm
Manitoba	OEL TWA (ppm)	20 ppm
New Brunswick	OEL TWA (mg/m ³)	121 mg/m ³
New Brunswick	OEL TWA (ppm)	25 ppm
Newfoundland & Labrador	OEL TWA (ppm)	20 ppm
Nova Scotia	OEL TWA (ppm)	20 ppm
Nunavut	OEL STEL (mg/m ³)	360 mg/m ³
Nunavut	OEL STEL (ppm)	75 ppm
Nunavut	OEL TWA (mg/m ³)	120 mg/m ³
Nunavut	OEL TWA (ppm)	25 ppm
Northwest Territories	OEL STEL (mg/m ³)	360 mg/m ³
Northwest Territories	OEL STEL (ppm)	75 ppm
Northwest Territories	OEL TWA (mg/m ³)	120 mg/m ³
Northwest Territories	OEL TWA (ppm)	25 ppm
Ontario	OEL TWA (ppm)	20 ppm
Prince Edward Island	OEL TWA (ppm)	20 ppm
Québec	VEMP (mg/m ³)	97 mg/m ³
Québec	VEMP (ppm)	20 ppm
Saskatchewan	OEL STEL (ppm)	30 ppm
Saskatchewan	OEL TWA (ppm)	20 ppm
Yukon	OEL STEL (mg/m ³)	720 mg/m ³
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m ³)	240 mg/m ³
Yukon	OEL TWA (ppm)	50 ppm

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Face shield.



Materials for Protective Clothing: Corrosionproof clothing.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses. Face shield.

Skin and Body Protection: Corrosionproof clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations Revision Date: 05/06/2025 Date of issue: 08/06/2014

Version: 1.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Slightly milky
Odor	: Mild
Odor Threshold	: Not available
pH	: 12 - 13
Relative Evaporation Rate (butylacetate=1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Specific Gravity	: 1.1
Solubility	: Not available
Partition coefficient: n-octanol/water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Thermal decomposition generates : Corrosive vapors.
Chemical Stability: Stable under recommended handling and storage conditions (see Section 7).
Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
Conditions to Avoid: Extremely high or low temperatures. Incompatible materials.
Incompatible Materials: strong acids. Strong bases. Strong oxidizers.
Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Corrosive vapors. Sulfur oxides.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified
LD50 and LC50 Data: Not available
Skin Corrosion/Irritation: Causes severe skin burns and eye damage.
pH: 12 - 13
Serious Eye Damage/Irritation: Causes serious eye damage.
pH: 12 - 13
Respiratory or Skin Sensitization: Not classified
Germ Cell Mutagenicity: Not classified
Teratogenicity: Not available
Carcinogenicity: Not classified
Specific Target Organ Toxicity (Repeated Exposure): Not classified
Reproductive Toxicity: Not classified
Specific Target Organ Toxicity (Single Exposure): Not classified
Aspiration Hazard: Not classified
Potential Adverse Human Health Effects and Symptoms: Harmful if swallowed.



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations Revision Date: 05/06/2025 Date of issue: 08/06/2014

Version: 1.0

Symptoms/Injuries After Inhalation: May cause respiratory irritation.
Symptoms/Injuries After Skin Contact: Highly corrosive to skin.
Symptoms/Injuries After Eye Contact: Causes serious eye damage.
Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.
Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

2-Butoxyethanol (111-76-2)	
LD50 Oral Rat	470 mg/kg
LD50 Dermal Rat	220 mg/kg
LC50 Inhalation Rat	450 ppm/4h
ATE US (vapors)	3.84 mg/l/4h
Pentasodium triphosphate (7758-29-4)	
LD50 Oral Rat	3100 mg/kg
LD50 Dermal Rabbit	> 7940 mg/kg
Sodium xylene sulfonate (1300-72-7)	
LD50 Oral Rat	1000 mg/kg
Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)	
LD50 Oral Rat	775 mg/kg
LD50 Dermal Rat	2000 mg/kg
2-Butoxyethanol (111-76-2)	
IARC Group	3
National Toxicity Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life.

2-Butoxyethanol (111-76-2)	
LC50 Fish 1	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
EC50 Daphnia 1	1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)	
LC50 Fish 1	3 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	2.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Persistence and Degradability Not available

Bioaccumulative Potential

2-Butoxyethanol (111-76-2)	
Log Pow	0.81 (at 25 °C)
Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)	
Log Pow	2 (at 23 °C)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
 Rules and Regulations Revision Date: 05/06/2025 Date of issue: 08/06/2014

Version: 1.0

SECTION 14: TRANSPORT INFORMATION

14.1 In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (Contains Disodium trioxosilicate)
 Hazard Class : 8
 Identification Number : UN1760
 Label Codes : 8
 Packing Group : III
 Marine Pollutant : Marine pollutant (Benzenesulfonic acid, C10-16-alkyl derivatives)
 ERG Number : 154



14.2 In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (Contains Disodium trioxosilicate)
 Hazard Class : 8
 Identification Number : UN1760
 Packing Group : III
 Label Codes : 8
 EmS-No. (Fire) : F-A
 EmS-No. (Spillage) : S-B



14.3 In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (Contains Disodium trioxosilicate)
 Packing Group : III
 Identification Number : UN1760
 Hazard Class : 8
 Label Codes : 8
 ERG Code (IATA) : 8L



14.4 In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (Contains Disodium trioxosilicate)
 Packing Group : III
 Hazard Class : 8
 Identification Number : UN1760
 Label Codes : 8
 Marine Pollutant (TDG) : Marine pollutant (Benzenesulfonic acid, C10-16-alkyl derivatives)



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Filter & Tile Cleaner	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
2-Butoxyethanol (111-76-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Pentasodium triphosphate (7758-29-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Sodium xylene sulfonate (1300-72-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

US State Regulations

2-Butoxyethanol (111-76-2)
U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
 Rules and Regulations Revision Date: 05/06/2025 Date of issue: 08/06/2014

Version: 1.0

Pentasodium triphosphate (7758-29-4)
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

Filter & Tile Cleaner	
WHMIS Classification	Class E - Corrosive Material
2-Butoxyethanol (111-76-2)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
Listed on the Canadian Ingredient Disclosure List	
IDL Concentration 1 %	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Pentasodium triphosphate (7758-29-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

Sodium xylene sulfonate (1300-72-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Benzenesulfonic acid, C10-16-alkyl derivatives (68584-22-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date : 08/06/2014
 Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B



Filter & Tile Cleaner

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 /
Rules and Regulations Revision Date: 05/06/2025 Date of issue: 08/06/2014


Version: 1.0

Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H401	Toxic to aquatic life
H402	Harmful to aquatic life

NFPA Health Hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA Fire Hazard : 1 - Must be preheated before ignition can occur.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 1 Slight Hazard

Physical : 0 Minimal Hazard

Party Responsible for the Preparation of This Document

Lo-Chlor, LLC
5841 Powerline Rd. Suite 202
Fort Lauderdale, FL 33309
954-491-9810

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS